What is claimed is:

- 1 1. A handwritten character recognition apparatus
- 2 having a character string input area of a size that allows
- 3 a plurality of characters to be handwritten thereon for
- 4 a user to input a handwritten character string, comprising:
- 5 a coordinate string detection unit operable to detect
- 6 a coordinate string of each stroke that makes up an input
- 7 handwritten character string,
- 8 an input completion judgement unit operable to judge,
- 9 when a first coordinate of one of the strokes is detected
- 10 in a first area which is at a side of the character string
- 11 input area where writing of the handwritten character
- 12 string starts, whether an input of an immediately preceding
- 13 handwritten character string is complete, and
- 14 a segmentation recognition unit operable to segment,
- 15 when the input completion detection unit judges the input
- 16 to be complete, stroke strings for each character from all
- 17 the strokes of the immediately preceding handwritten
- 18 character string, recognize each character, and output a
- 19 character string which is a recognition result.
 - 1 2. A handwritten character recognition apparatus
- 2 according to Claim 1, wherein the input completion

- 3 judgement unit includes:
- 4 a first coordinate judgement unit operable to judge,
- 5 when an X value of a first coordinate of a stroke is X1
- 6 or less, X1 being a width of the first area, that the first
- 7 coordinate is in the first area.
- 1 3. A handwritten character recognition apparatus
- 2 according to Claim 2, wherein the input completion
- 3 judgement unit further includes:
- 4 an X1 setting unit operable to receive a value of X1
 - 5 according to a size of a handwritten character written by
- 6 the user, the first coordinate judgement unit judging
- 7 according to the received value of X1.
- 1 4. A handwritten character recognition apparatus
 - according to Claim 1, wherein the input completion
- 3 judgement unit includes:
- 4 an input time measurement unit operable to measure
- 5 a first input time which is an input time of a first
- 6 coordinate of each stroke, and a second input time which
- 7 is an input time of a last coordinate of each stroke, and
- 8 a time judgement unit operable to judge, when a time
- 9 difference between the first input time of a stroke and
- 10 a second input time of an immediately preceding stroke is

- 11 at least a predetermined time, that the input of the
- 12 immediately preceding handwritten character string is
- 13 complete.
 - 1 5. A handwritten character recognition apparatus
 - 2 according to Claim 4, wherein the input completion
 - 3 judgement unit includes:
- a judgement time setting unit operable to receive a
- 5 setting of a predetermined time according to a speed of
- 6 input of handwriting of the user, the time judgement unit
- 7 judging that the input of the immediately preceding
- 8 handwritten character string is complete when the input
- o manawileten character sering is sumplied in
 - thereof ceases for at least the predetermined time.
- 1 6. A handwritten character recognition apparatus
- 2 according to Claim 1, wherein the input completion
- 3 judgement unit includes:
- 4 a stroke area judgement unit operable to judge that
- 5 the input of the immediately preceding character string
- 6 is complete when a first coordinate of a stroke thereof
- 7 is in a second area which is an area at the opposite side
 - of the character string input area to the first area.
- 1 7. A handwritten character recognition apparatus

- 2 according to Claim 6, further comprising:
- 3 a display unit, positioned under a transparent tablet
- 4 which makes up the character string input area, operable
- 5 to successively display strokes by linking the coordinates
- 6 of each coordinate string detected by the coordinate string
- 7 detection unit by line segments, and
- 8 an area display control unit operable to control a
- 9 display state of the display unit so as make the first area
 - and the second area visually recognizable.
- 1 8. A handwritten character recognition apparatus
 2 according to Claim 1, further comprising:
- 3 a display unit operable to display a stroke by linking
- 3 a display diffe operable to display a scioke by linking
- 4 the coordinates of each coordinate string successively
- 5 detected by the coordinate string detection unit, and
- 6 an erasing unit operable to erase all strokes that
- 7 make up the immediately preceding handwritten character
- 8 string when the input completion judgement unit judges the
- 9 input thereof to be complete.
- 1 9. A handwritten character recognition apparatus
- 2 according to Claim 1, further comprising:
- 3 a display unit, positioned under a transparent tablet
- 4 which makes up the character string input area, operable

- 5 to successively display strokes by linking coordinates
- 6 detected by the coordinate value detection unit by line
- 7 segments, the coordinate string detection unit being a
- 8 transparent tablet, and
- 9 a first area display control unit operable to control
- 10 $\,$ a display state of the display unit so as make the first
- 11 area and the second area visually recognizable.
 - 10. A handwritten character recognition apparatus having a character string input area of a size that allows
 - a plurality of characters to be handwritten thereon for a user to input a handwritten character string, comprising:
- a coordinate string detection unit operable to detect
 - a coordinate string of each stroke that makes up an input
- 7 handwritten character string,
- 8 a display unit, positioned under a transparent tablet
- $\, 9 \,$ which makes up the character string input area, operable
- 10 to successively display strokes by linking coordinates
- 11 detected by the coordinate value detection unit by line
- 12 segments, the coordinate string detection unit being a
- 13 transparent tablet,
- 14 a first line segment erasing unit operable to erase
- 15 line segments displayed in a judgement area which is an
- 16 area a predetermined distance apart from the last

17

18

32

33

34 35

coordinate of a stroke detected by the coordinate string detection unit in a direction towards the side of the

character string input area where writing of the 19

handwritten character string starts,

an input completion judgement unit operable to judge, when the coordinate string detection unit detects the first coordinate of a stroke in the judgement area, that an input of an immediately preceding handwritten character string

a second line segment erasing unit operable to erase remaining line segments from the character string input area, excluding the line segments in the judgement area, and

a segmentation recognition unit operable to segment, when the input completion detection unit judges the input to be complete, stroke strings for each character from all the strokes of the immediately preceding handwritten character string, recognize each character, and output a character string which is a recognition result.

A program for use with a handwritten character 1

recognition apparatus having a character string input area 2

of a size that allows a plurality of characters to be 3

handwritten thereon for a user to input a handwritten

5 character string, the program realizing on a computer:

a coordinate string detection unit operable to detect 6

a coordinate string of each stroke that makes up an input 7

8 handwritten character string,

17 £18 0

20

7

an input completion judgement unit operable to judge, 9

10 when a first coordinate of one of the strokes is detected

in a first area which is at a side of the character string 11

input area where writing of the handwritten character 12

©13 string starts, whether an input of an immediately preceding 113 0114 1115 0116

handwritten character string is complete, and

a segmentation recognition unit operable to segment, when the input completion detection unit judges the input to be complete, stroke strings for each character from all the strokes of the immediately preceding handwritten character string, recognize each character, and output a character string which is a recognition result.

A computer-readable recording medium for use with a 1

2 handwritten character recognition apparatus having a

3 character string input area of a size that allows a

plurality of characters to be handwritten thereon for a 4

user to input a handwritten character string, the medium 5

6 recording a program that realizes on a computer:

a coordinate string detection unit operable to detect

- 8 a coordinate string of each stroke that makes up an input
- 9 handwritten character string,
- 10 an input completion judgement unit operable to judge,
- 11 when a first coordinate of one of the strokes is detected
- 12 | in a first area which is at a side of the character string
- 13 input area where writing of the handwritten character
- 14 string starts, whether an input of an immediately preceding
 - handwritten character string is complete, and

a segmentation recognition unit operable to segment, when the input completion detection unit judges the input to be complete, stroke strings for each character from all the strokes of the immediately preceding handwritten character string, recognize each character, and output a character string which is a recognition result.